



4-Post Boat Lifts

- All Aluminum and Stainless Steel Construction
- Available in Multiple Drive Configurations including:
 - Direct Drive (no belts or chains)
 - Sealed Gearbox Belt Drive
 - Ultra Fast Direct Drive (H2)
- Marine Duty Stainless Steel Motors
- "Quick Adjust" Stainless Steel Cables
- Heavy Duty, easily adjustable Guide Poles
- Extruded Aluminum Bearing Blocks
- Welded Construction (not bolted)
- Aluminum Pulleys with Stainless Steel Axle Bolts & Grease Fittings
- Optional SEArmor Corrosion Resistant Package
- 10 Year Limited Warranty

Additional Options:

- Wireless Remote Control
- Limit Switch with Auto Stop
- Aluminum Bunks (Up to 16,000 lbs.)

***See our "Complete list of Other Accessories"



Specifications

Size	Top Carrier Dimensions	Lifter Beam Dimensions	Horse Power	Volt and Amperage	Cable Size and Length	Vertical Travel	Bunks	Pile Size
4,500 lb.	5" x 12' 6" Channel	6" x 11'0" I-Beam	(2) 3/4 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 20' Stainless Steel	12'+	3" x 8" x 12' Carpeted Bunks	(4) 8" Pilings
7,000 lb.	5" x 12' 6" Channel	6" x 12'0" I-Beam	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 20' Stainless Steel	12'+	3" x 8" x 12' Carpeted Bunks	(4) 8" Pilings
10,000 lb.	6" x 12'6" Channel	8" x 12'6" I-Beam	(2) 3/4 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 32' Stainless Steel	12'	3" x 8" x 12' Carpeted Bunks	(4) 8" Pilings
13,000 lb.	7" x 12'6" Channel	8" x 12'6" I-Beam	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 32' Stainless Steel	12'	3" x 10" x 12' Carpeted Bunks	(4) 8" Pilings
16,000 lb.	7" x 12'6" Channel	10" x 14' I-Beam	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 32' Stainless Steel	12'	3" x 10" x 14' Carpeted Bunks	(4) 10" Pilings
20,000 lb.	8" x 12'6" Channel	10" x 14' I-Beam	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 48' Stainless Steel	12'	3" x 10" x 14' Carpeted Bunks	(4) 10" Pilings
24,000 lb.	8" x 15'0" Channel	12' x 15' I-Beam	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 48' Stainless Steel	12'	3" x 12" x 18' Carpeted Bunks	(4) 10" Pilings
30,000 lb. (w/remote)	8" x 15'0" Channel	12" x 16' I-Beam	(4) 1 HP Stainless Steel*	240V/30A	3/8" x 50' Stainless Steel	12'	3" x 12" x 20' Carpeted Bunks	(4) 12" Pilings

*Stainless Steel Motors are Standard on all Direct Drive and H2 High Speed Direct Drive Lifts Only